VISIBLE EMISSION NOT	ATIONS				
Inspector: RICK PA	LOMO			•	
Date of Inspection: 3/1/	1				
Shift: 1 st Shift or 2 nd Sr	nift Ti	me: 5:00AM	·	·	
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments		
Visible Emission From Shaker	NOR				
Visible Emission From Discharge Conveyor System	NOR				


- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				
Inspector: James	rederide				
Date of Inspection:			erra,		
Shift: 1st Shift: or 2nd Sh	ift Ti	me: 1700			
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL			Comments	
Visible Emission From Shaker	NOR	described and the second of th			
Visible Emission From Discharge Conveyor System	NoR	entre de la constitución de la c			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS Inspector: Date of Inspection: 2nd Shift Shift: 1st Shift or Time: 5:300 AM 2nd Unit Visual Comments Inspection NORMAL **ABN**ORMAL Visible Emission From Shaker NOR Visible Emission From Discharge Conveyor System NOR

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	ATIONS			
Inspector:				
Date of Inspection: 3/6	/		ATOU	Down
Shift: Shift or 2 nd Sh	nift Ti	me: 017:00		
Unit - Land - La	Visual Inspection <u>NOR</u> MAL or ABNORMAL			nments
Visible Emission From Shaker	Nor			od a Photograf County (Popularia County) and county). Note that followed the county and county of the county of th
Visible Emission From Discharge Conveyor System	Non	salesation.		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Tames F	redered			
Date of Inspection:	Z ~ []			
Shift: 1 st Shift or 2 nd Sh	ift Tim		· ·	
7.5	2 /	1700		
Unit_	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:				
Date of Inspection: 3/4	·			
Shift: (1 st Shift or 2 nd Sh	nift Ti	me: @ 17:00		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Non	_		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		1		
Inspector: S. Guzi	2020				
Date of Inspection: 3 5					
Shift: 1st Shift or 2nd Sh	ift Ti	me: 50M			
Unit	Visual Inspection <u>NOR</u> MAL or			Comments	
Visible Emission From Shaker	<u>ABN</u> ORMAL				
Vie.	MOR	5.0.3	DONN		
Visible Emission From Discharge Conveyor System	NOR	S.D.S	NOON.)	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	naton			
Date of Inspection: 3/6/	u''			
Shift: (1st Shift or 2nd Sh	ift Ti	me: /700		
Unit 1	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Non	4	-	
Visible Emission From Discharge Conveyor System	N_{c}			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick PAL	ome			
Date of Inspection: 3/7/	11			
Shift: 1 st Shift or 2 nd /Sh	الغب	me: 5:00AM		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR	Viversing setting to a proper design of the property of the pr		
Visible Emission From Discharge Conveyor System	NOR	According to the second		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:) _{وځ} ر			
Date of Inspection:	3/7/11			
Shift: (1 st Shift) or 2 nd Sh	ift Ti	me: @ 17:00		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	New	Authoriza		
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS					
Inspector: Rick PALC	emo					
Date of Inspection: 3/6/	1(
Shift: 1 st Shift or 2 nd Sh	nift Ti 2nd	me: 51:00Ar				
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL			omments		
Visible Emission From Shaker	NOR	Source Control of the				
Visible Emission From Discharge Conveyor System	NOR	And control of the second of t				•

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	The			
Date of Inspection:	3/8/1	l		
Shift: (1 st Shift) or 2 nd Sh	ift Ti	me: C17:00		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	Noe	and the second s		
Visible Emission From Discharge Conveyor System	Non	Пара		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE FINISSION NO LA	TIONS		
Inspector: RICK P	HOMO		
Date of Inspection: 3/9/	1 (
Shift: 1 st Shift or 2 nd Sh	ift 2nd Ti	ime: 5:00AM	
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments
Visible Emission From Shaker	NOR	**************************************	
Visible Emission From Discharge Conveyor System	NOR		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE FIMISSION NOTA	TIONS			
Inspector: KURT	WALTER	S		
Date of Inspection: 3/9 /	1			
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 5:00AM		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector: RICK PALC	OMO			
Date of Inspection: 3/10/	/11			
Shift: 1 st Shift or 2 nd Sh	nift Ti 2n d	me: 5:00AM		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOR	vice CH394 Prints and all an extra translating page.		
Visible Emission From Discharge Conveyor System	NOR	newspectual production of the Assessment and Constitution of the Assessment and Consti		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: The				
Date of Inspection: $\sqrt{3/6}$				
Shift: (1 st Shift or 2 nd Sh	nift Ti	me: @ 17:00		
	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Non	guageparativa		
Visible Emission From Discharge Conveyor System	Non	,		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: RICK PA	tlome			
Date of Inspection: 3/11	/11			
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 5:00AM		
Unit (1997)	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR	e-baselingscollaborate production grand gr		
Visible Emission From Discharge Conveyor System	NOR	**************************************		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector:	4				
Date of Inspection:	11/11				
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 17:00			
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Co	mments	
Visible Emission From Shaker	Nor	Collections			
Visible Emission From Discharge Conveyor System	Non	v			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS			
Inspector:	Compter	}		
Date of Inspection:	3/12/11			
Shift: 1 st Shift or 2 nd Sh	lift 2nd Til	me: 500 AM		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nov			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

Inspector:	7			
Date of Inspection:	3/12/11			
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: [17:00		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nac	ectropics.		
Visible Emission From Discharge Conveyor System	Nar	_{grand} e.		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		_	
Inspector:	d Compton			
Date of Inspection:	13/11	·.		
Shift: 1 st Shift or (2 nd)Sh	nift 2 Ti	me: SooAM		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nor	der gelegen die der betreigigt, der	gare entiring de bella con ming gen begle desti mind beng 1850 min. (rengg i entirpe i de bengan hijde der pou administr	unic tangin, galiji. Landan gili aya mashara da karagaparak iliya a 175g ti silka galimba di ing paringa a cosab ind
Visible Emission From Discharge Conveyor System	N _o C			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITC. .NG LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

Condition D.1.17 Record Keeping Requirements for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distil PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distil Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough is detected as stated below under Note.

and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

and the talks are in the
D.1.14 CARBON ADSORPTION SYSTEM INSPECTION
D.1.14 CARBON ADSORT 17-
Inspector:
Date of Inspection: Time: 500 AM
pate
Shift: (First or Second)
Monitor ID: Min Rae 2000
theretion Gases:
Instrument Calibration Stylene 106 PPV
Background Instrument Reading: O C Exhaust
Background

Carbon
Replacement
Replacement
Roll Off Box
Offsite Com

Visual

Insp.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	L			
Date of Inspection:	3/13/11			
Shift: (1 st Shift) or 2 nd Sh	nift Ti	ime: 0 /7 00		·
Unit (1997)	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nex			
Visible Emission From Discharge Conveyor System	Nat	Applino		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: Rick PAC	OMO				
Date of Inspection: 3/14	111				
Shift: 1 st Shift or 2 nd Sh	nift 2nd Ti	ime: 5:00 An	1		
Unit Company of the Company of the C	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL			nments	
Visible Emission From Shaker	NOR	** Landaughtus mussikund yellindirentilitimustativasilysellysellysellustativaminestilitimustativas			
Visible Emission From Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector:	no .			
Date of Inspection:	3/14/11			
Shift: (1st Shift) or 2nd Sh	nift Ti	me: @ 17:00		
Unit	Visual Inspection NORMAL or		Comments	
	<u>ABN</u> ORMAL			
Visible Emission From Shaker	Nol	the state of the s		
Visible Emission From Discharge Conveyor System	Nor	yaanne		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	RIONS			
Inspector: Rick PA	LOMO			
Date of Inspection: 3/15	lil	·		
Shift: 1 st Shift or 2 nd Si	nift Ti 2nd	me: 5:00AM		
Unit	Visual Inspection NORMAL or	Transfer of the second of the	Comments	
	<u>ABN</u> ORMAL			
Visible Emission From Shaker	NOR	***		
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	RIONS							
Inspector:								
Stoyau								
Date of Inspection:	3/15/11							
Shift: (1st Shift) or 2nd St	off Ti	me: 🗘 👝						
Sint. Ching of 2 of	1116 11	U17:00	5					
Unit Control	Visual Inspection <u>NOR</u> MAL Or ABNORMAL				omments			
Visible Emission From Shaker	Nac	Silveryori	ATOU	Down		omiglianistico, leng se saredirecturation de	and the state of t	
Visible Emission From Discharge Conveyor System	NOL		V	/				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick PALO	OMO			
Date of Inspection: 3/16/1				
Shift: 1 st Shift or 2 ^{ndt} Sh 2nd	nift Ti	me: 5:00 AM		1
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				
Inspector: -	100~				
Date of Inspection:	V1				
3/16		A STATE OF THE STA			
Shift: 1st Shift or 2nd Sh	ift Ti	me: @ 17-00			
Unit	Visual		Cor	nments	
	Inspection NORMAL				
	or ABN ORMAL				
Visible Emission From Shaker	Nor	_	Arou	Down	
Visible Emission From	W tM			w	
Discharge Conveyor System	1 1010				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

AIOIDEL FIMIOCICIA IAO IA	110110			
Inspector: RICK PAL	omo			
Date of Inspection: 3/17	/11			
Shift: 1 st Shift or 2 nd Sh	nift T	ime: 5:GOAM		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR	e de la companya del companya de la companya de la companya del companya de la co		
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		•	
Inspector: A				
Date of Inspection:	18/11			
Shift: 1st Shift or 2nd Sh	nift Ti	me:@(7:00		
Unit	Visual Inspection NORMAL		Comments	
	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	NW	50000,	ATOU DOWN	
Visible Emission From Discharge Conveyor System	NOL		d	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS,			
Inspector: Ted	Compton			
Date of Inspection: 3/18	(11			
Shift: 1 st Shift or (2 nd Sh	lift Ti	me: 500 AM		
	2n0	3 00 ITV 1		
Unit	Visual Inspection NORMAL Or ABNORMAL		Comments	
Visible Emission From Shaker	Nor	Фация, предерждения от полительной подоложения полительной подоложения полительной подоложения в подоложения в	and advantage and account.	
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		
Inspector:	生		
Date of Inspection:	3/18/1		
Shift: (1 st Shift) or 2 nd Sh	nift Ti	me:C (7: 06	
Unit	Visual Inspection NORMAL or		Comments
Visible Emission From Shoker	ABNORMAL		
Visible Emission From Shaker	Non	**Graphos _s	
Visible Emission From Discharge Conveyor System	NoL	1986	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

				•
VISIBLE EMISSION NOTA	ATIONS			
Inspector: Ted Co	mpton			
Date of Inspection: $3/9$	(", /			
Shift: (1st Shift or 2nd Si	nift 15 T	me: 1700		
Unit	Visual		Comment	
area comments of the decision of the second	- <u>NOR</u> MAL		and the second of the second o	
	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	4/ 0	When the control of t	•	
Visible Emission From	Nor			
Discharge Conveyor System	Nac		nam.	
	(V V /5 V			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector:	54			
Date of Inspection:	3 bolii	_		
Shift: (1 st Shift) or 2 nd Sh	nift Ti	ime: 0 17:00	1	
Unit '	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Nor	Antonia		
Visible Emission From Discharge Conveyor System	Non	-		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Rick PA	omo			
Date of Inspection: 3/21	/11			
Shift: 1 st Shift or 2 nd Sh		me: 5:00 AM		
Unit:	Visual Inspection <u>NOR</u> MAL OI ABNORMAL		Comments	
Visible Emission From Shaker	NOR	**************************************		
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	
Inspector:	
Date of Inspection:	
Shift: (1st Shift)or 2nd Shift Time:	
Unit Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	
Visible Emission From Discharge Conveyor System	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		
Inspector: Rick R	ALOMO		
Date of Inspection: 3/22	2/11		
Shift: 1 st Shift or 2 nd Sh	ift Ti	me: 5:00AM	
Unit	Visual Inspection NORMAL or ABNORMAL		Comments
Visible Emission From Shaker	NOR	Prolitation in coloration control devices	
Visible Emission From Discharge Conveyor System	NOR		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		·		
Inspector:	ga.				
Date of Inspection:	3/22/11				
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: (217:00			
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comme	nts	
Visible Emission From Shaker	Noe		Taktor Calibra (Annais an Meale Island an Takey melegia dina di digunale di dalah (Anda) a siban	and the second s	real Control of the C
Visible Emission From Discharge Conveyor System	No				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector:				
7 Doel	 		4	
Date of Inspection: U	1-3/1			
0	123/il		-	
Shift: (1st Shift or 2nd Sh	nift Ti	me:C17:00		
	I in a construction of the	C17.00		
Unit	Visual	1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990	Comments	
	Inspection	State of the State		and the second of the second o
	<u>NOR</u> MAL		entropies and consistent that the second of the second	
	of .			
	<u>ABN</u> ORMAL			
Visible Emission From Shaker	1 2 2	(selliformum-		
	Nat			
Visible Emission From				
Discharge Conveyor System	1 100			
	1 VOYL			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		_	
Inspector: RICK PAL	LOMO			
Date of Inspection: 3/24/	1)			
Shift: 1 st Shift or 2 nd Sh		ime: 5:00AM		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments Comments	
Visible Emission From Shaker	NOR	"Падання промощения на поставления развити на предоставления на пр		
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		 •		
Inspector:					
	14/11				
Shift: (1 st Shift or 2 nd Sh	nift T	ime: @ 17:00			
Unit	Visual Inspection NORMAL		Comments		
	or ABNORMAL			1900 1999 1900 1999 1900 1999	
Visible Emission From Shaker	Nor	garage.			
Visible Emission From Discharge Conveyor System	Non	and the same of th			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: RICK PA	Lomo			
Date of Inspection: 3/25	/11			
Shift: 1 st Shift or 2 nd Sh	ift d Ti	me: 5: <i>6</i> 0		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector:	Aur				
Date of Inspection:	3/25/11				
Shift: (1 st Shift) or 2 nd St	nift Ti	me: @17:00			
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Commen		
Visible Emission From Shaker	Noc			Garantin da esta de la constitución de la constituc	and Article Argue de Sacre (Mare Sarier) de l'Article Sarie Arre de Level de Level (Article Sarier) de Level (
Visible Emission From Discharge Conveyor System	Nor	solver			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	
Inspector:	
Date of Inspection:	
Shift: 1st Shift or Shift 2nd Time: 506 AM	
Unit Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	
Visible Emission From Discharge Conveyor System Nor	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	Pol .			
Date of Inspection:	3/26/1	1		
Shift: (1 st Shift) or 2 nd Sh	ift Ti	me: 0 17:00		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nar	terformer		
Visible Emission From Discharge Conveyor System	Nac	populari de la companio de la compa		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS			
Inspector:				
Date of Inspection:	3/27/11			
Shift: (1st Shift) or 2nd Sh	nift Ti	ime: @ 17:00		
Unit (1)	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Non			
Visible Emission From Discharge Conveyor System	Non	- Contraction of the Contraction		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				÷
Inspector:	ompton				
Date of Inspection:	3/11				
Shift: 1 st Shift or 2 nd St	nift Ind Ti	me: 500 AM			
Unit	Visual Inspection NORMAL or ABNORMAL		Commen		
Visible Emission From Shaker	Nor			C. Things of the American Community of the Community of t	
Visible Emission From Discharge Conveyor System	Nac				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	Ace.			
Date of Inspection:	3/28/11			
Shift: (1st Shift) or 2nd St	nift Ti	ime: @17:00		
Unit	Visual Inspection <u>NOR</u> MAL or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Nac			
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		·	
Inspector: Rick PA	Lamo			
Date of Inspection: 3/2	9/11			
Shift: 1 st Shift or 2 nd Sh	2nd T	me: 5:00 AM		
Unit	Visual Inspection <u>NOR</u> MAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOR	A		
Visible Emission From Discharge Conveyor System	NOR	American general final designation.		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Stagne				
Date of Inspection:	129/11			
Shift: (1 st Shift or 2 nd Sh	nift Ti	me: @17:00		
Unit The state of the state of	Visual Inspection <u>NOR</u> MAL Or		Comments	
Visible Emission From Shaker	ABNORMAL NOV			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS				
Inspector: RICK PA	LOMO				
	0/11				
	nift Ti 2nd	ime: 5! 0	MAOC		
Unit	Visual Inspection <u>NOR</u> MAL Or ABNORMAL			Comments Thracesplays	
Visible Emission From Shaker	NOR				
Visible Emission From Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		****			
Inspector:	# 0 š					
Date of Inspection:	3/30/11					
Shift: (1st Shift) or 2nd Sh	nift T	me: (17 ° 00				
Unit	Visual Inspection NORMAL of ABNORMAL			ments		
Visible Emission From Shaker	Nord		encentral control and a contro	kan in and a kan a diang diang diang diang a kan a	aan dan ka	Anadolis de la companya de la compa
Visible Emission From Discharge Conveyor System	Non	gyman				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: RICK PA	Lomo			
Date of Inspection: 3/31	111			
Shift: 1 st Shift or 2 nd Sh	iift Ti 2nd	me: 5:00 AM		
Unit	Visual Inspection	The state of the s	Comments	
	<u>NOR</u> MAL		and the second of the second o	
	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	NOR	- ng ggggassa and an shi an han an a		
Visible Emission From				
Discharge Conveyor System	NOR	And the second s		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTAT	IONS			
Inspector:	nul,			
Date of Inspection:	1-1	· · · · · · · · · · · · · · · · · · ·		
3	> 13 1 1 1			
Shift 1st Shift or 2nd Shift	τ !!	me: 017:00		
Unit	Wall Visual	$K_{2}=\{1,\ldots,K_{n}\}$	Comments	
	Inspection <u>NOR</u> MAL	en de la companya de La companya de la co		
	or ABNORMAL	diginal distribution of the second of the se		
Visible Emission From Shaker			ATOU DOWN	
· · ·	Non		A I Du Dawy	
Visible Emission From	Nico			
Discharge Conveyor System	Non	grand-		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.